

Vacuum Insulation Panel for Building (VIP) Technical Data Sheet



Product Profile

Vacuum insulation panel (VIP) is a new type of super insulation material emerging based on vacuum insulation technology. They combine the advantages of both vacuum insulation and micro-porous insulation methods, achieving ultimate thermal insulation performance.

Zerothermo's vacuum insulation panels are made of nano-scale composite core materials with excellent thermal insulation properties, encapsulated in high-barrier films under vacuum conditions. They minimize heat conduction, convection and radiation, block heat transfer, and possess high-efficiency thermal insulation capabilities.

These panels are widely used in fields such as thermal insulation for internal and external building walls, and integrated thermal insulation and decoration panels.



Product Features

- Excellent Thermal Insulation: Thermal insulation performance is 5-8 times better than that of traditional thermal insulation materials.
- High-Efficiency Fire Resistance: Made mainly of inorganic core materials, achieving Class A fire protection.
- Ultra-Thin Insulation Layer: The high-efficiency thermal insulation performance can effectively reduce the thickness of the insulation layer and increase usable space.
- Long Service Life: Unique core material structure without the need for getters, with a service life of up to 50 years.
- Green and Pollution-Free: Certified by both ROHS and REACH.

Technical Data

Thermal Conductivity $\leq 0.006\text{W}/(\text{m}\cdot\text{K})$ or $\leq 0.008\text{W}/(\text{m}\cdot\text{K})$

Initial Value (25°C)

Thermal Conductivity $\leq 0.025\text{W}/(\text{m}\cdot\text{K})$

Ventilated (25°C)

Initial Heat Transfer Coefficient (25°C) $0.23\text{W}/(\text{m}^2\cdot\text{K})$ (厚度=20mm)

Internal Air Pressure (20°C) $\leq 5\text{mbar}$

Density $280\text{Kg}/\text{m}^3$ - $320\text{Kg}/\text{m}^3$

Puncture Strength $\geq 18\text{N}$

Tensile Strength $\geq 100\text{kPa}$

Compressive Strength $\geq 100\text{kPa}$

Expansion Rate Perpendicular to the Panel $\leq 10\%$
Surface After Puncture

Fire Rating **Class A**

Service Life **50 Years**

Remark

-Custom sizes are available upon customer request. For special requirements, please contact us.

Dimensions and Tolerances

Length	≤1200mm
Width	≤800mm
Thickness	5~40mm
Length and Width Tolerances	±10mm
Thickness Tolerance	±2mm
Film Material and Folding Method	Metalized Barrier Film Glass Fiber Film Three-Side Sealing
Package & Delivery	Carton + Pallet

Application Fields

